

## **Corporate colours**

| Pantone<br>for offset, book and<br>screen printing            | Pantone 281 C                           | Pantone 485 C                         | Pantone 130 C                             |
|---|---|---------------------------------------|---|
| CMYK*<br>for 4 colour printing                                | C100/M85/Y5/K35                         | M96/Y100                              | M35/Y100                                  |
| <b>RGB</b> for screen   | R0, G38, B100                           | R213, G43, B30                        | R240, G171, B0                            |
| NCS<br>for paint and coatings<br>+ for Multicolor equipment   | NCS 6040R 80B                           | NCS 1090Y 90R                         | NCS 1070 Y 20 R                           |
| <b>RAL</b> for lacquer  | RAL 5022                                | RAL 3020                              | RAL 1003                                  |
| <b>3M</b><br>for foil   | 3M 100-003                              | 3M 100-368                            | 3M 100-25                                 |
| <b>Avery</b> for foil   | 723 Dark Blue**<br>933 Midnight Blue*** | 726 Medium Red**<br>906 Medium Red*** | 904 Crome Yellow**<br>904 Crome Yellow*** |
| <b>Avery</b><br>for lightbox use<br>Graphics Translucent film | 5545 QM Steel Blue                      | 5519 QM Apple Red                     | 5511 Melon Yellow                         |

<sup>\*</sup> Please note that cmyk values indicated in this guideline are taken from "Pantone® color bridgeTM coated EURO" (Pantone EC).

## **Secondary colours**

| occondary coroars                                  |                                    |                  |                         |                         |  |  |
|--|------------------------------------|------------------|-------------------------|-------------------------|--|--|
|  |                                    |                  |                         |                         |  |  |
| Pantone<br>for offset, book and<br>screen printing |                                    | Pantone 429 C    | Pantone 429 C<br>(50 %) | Pantone 429 C<br>(25 %) |  |  |
| CMYK*<br>for 4 colour printing                     |                                    | C21/M11/Y9/K23   |                         |                         |  |  |
| RGB<br>for screen                                  |                                    | R165, G172, B175 |                         |                         |  |  |
| NCS <sup>1</sup>                                   |                                    |                  |                         |                         |  |  |
| <b>RAL</b> for lacquer, paint and coatings         | RAL 9010                           | RAL 7001         |                         |                         |  |  |
| <b>3M</b><br>for foil                              |                                    | 3M 100-003       |                         |                         |  |  |
| <b>Avery</b> for foil                              |                                    |                  |                         |                         |  |  |
| <b>Lacque</b> for packaging                        | Art. no. UP 3206<br>Coates Coating |                  |                         |                         |  |  |

<sup>\*</sup> Please note that cmyk values indicated in this guideline are taken from "Pantone® color bridgeTM coated EURO" (Pantone EC).

<sup>\*\*</sup> Economical – suitable for medium-life indoor and outdoor applications

<sup>\*\*\*</sup> Expensive – superb quality, up to 12-years' life even in the most challenging condictions

<sup>1)</sup> For Jotun Multicolor Hardware NCS S 2500 N is preferred on tinting machines and shakers. For Jotun Multicolor Colour Bar NCS S 2000 N or NCS 1000 N are both optional choice, and preferred over the NCS S 2500 N for other colour tools and interiors at POS.