

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of Norway.

This is to certify:

That the Surface materials and floor coverings with low flame-spread characteristics: paint systems

with type designation(s)
Primax Xtend / Jotun Super Durable 2908

Issued to
Jotun A/S
SANDEFJORD, Norway


is found to comply with the requirements in the following Regulations/Standards:
Regulation **(EU) 2018/773**,
item No. MED/3.18b. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2023-10-01**.

Issued at **Høvik** on **2018-10-02**

DNV GL local station:
Sandefjord



for **DNV GL AS**

Approval Engineer:
Thorvald Furuseth

Notified Body
No.: **0575**

.....
Roald Vårheim
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Product description

'Primax Xtend / Jotun Super Durable 2908'
Is a paint system consisting of:

1. 'Primax Xtend'
Zink-free powder coating.
Max. thickness: 90 µm (dry film thickness).
2. 'Jotun Super Durable 2908'
Lead-free, TGCI-free powder coating.
Max. thickness: 90 µm (dry film thickness).

Max. thickness (total system): 180 µm (dry film thickness).

Application/Limitation

Approved for use as low flame spread material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as paint systems on metallic surface with thickness of at least 2.25 mm.

Primer 'Primax Xtend':

- Approved colour: Light grey.
- Max. organic content: 57.8 wt% per dry film thickness.

Top coat 'Jotun Super Durable 2908':

- Approved colour: All colours.
- Max. organic content: 83.6 wt% per dry film thickness.

The product satisfies the requirement for maximum calorific value (ref. Solas Chapter II-2, Reg 5.3.2.2) without further testing.

Each product is to be supplied with its manual for its installation, use and maintenance.

Type Examination documentation

Test report no. S-04479-18 dated 19 September 2018 from Eurofins Expert Services, Finland.

Tests carried out

Tested according to IMO 2010 FTP Code Part 5 and Annex 2 item 2.2 and 2.3.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, MED Mark of Conformity and USCG approval number (see page 1).